## We're Always the First to See You

# U3io-XFace Premium








## **High Performance Multi Authentication** -

UBio-X Face Premium is equipped with a high-performance face recognition algorithm to quickly recognize the user's face accurately, even from a distance of up to 4m.

Through the use of multi mode, 4 people can be authenticated at same time and can be used in situation that requires a large number of simultaneous entry.





## **Support Multiple Authentication Method** -

By integrating with the XScan-FQ, XScan-FP, various authentication methods such as face, fingerprint, mobile key, QR code, password and card can be selected.

By utilizing 'and' & 'or' authorization method, it is able to select and use the authentication method according to the customer's needs.











FINGERPRINT QR Code PASSWORD





## Access & Virus Control for Safer Perimeter

According to contactless solution such as mask detection (3 levels), contactless visitor & event management and remote user registration can prevent virus infection.

Through the integration of Thermal Camera sensors, UBio-X Face Premium automatically measures body temperature and protect the perimeter 24/7.






## Secure Data Protection & Encryption

All biometric information is protected based on a technology that encrypts and saves as the minutia point used in the algorithm engine without saving the original image.

#### **SYSTEM CONFIGURATIONS**



## **SPECIFICATION**

Model Name  Model Image			UBio-X Face Premium
	NPU	O (2.3 TOPS)	
OS		Android 11	
MEMORY	Flash	16G eMMC 4G (LPDDR4)	
-	RAM type	8' (TFT IPS LCD)	
LCD	Resolution	800 X 1280	
Speaker		Audio Codec 1W	
MIC		Waterproof MIC	
Operating Temperature		-20℃~60℃	
Operating Humidity		0% ~ 90% non-condensing	
Weight  Dimension (W x H x D) mm		980g 143.3 X 289.5 X 23.8	
Temper		O	
IP Rating		IP55	
Certificates		KC / CE / FCC	
Biomatrics		Recognition Distance	0.5M~4M
	Face	Matching Speed	<1 sec
		Liveness Detection	0.5M ~ 2M 100.000
	FingerPrint	Template  Extractor / Matcher	MINEX certified and compliant
		Image Dimension	256*292 (12.6 *14.8 mm)
		Resolution	500 DPI
		Certification	Virdi, ISO 1974-2, ANSI-378
		LFD	0
	RF Read Range	EM	50 mm
		Smart Card	50 mm
		DESFIRE EV1 / EV2 / EV3 FELICA	45 mm
_		125KHz EM	All in One
RF	RF Option	13.56MHz Smart Card	
		Mifare (Plus)	
		Felica	
		ISO14443 A/B	
		ISO 15693 DESFIRE EV1 / EV2 / EV3	
		HID Prox	
		HID iCLASS SE/SR/Seos (Optional)	
Mobile Card		NFC	Support
IVIODIII CUIU		BLE	Support
	Image Sen0.sor		640 X 480
QR	Symbologies		1D / 2D
	FOV (H x V)		42° x 31.5°
UBio-X Key	Mobile Phone (IOS)  Mobile Phone (Android)		Iphone: iOS 10.0 or above / BLE4.2 or above  Android 6.0 or above / NFC Supported Device
	Encryption		Azure Key Vault / AES-128
	Recognition Distance		10cm (difference in models)
	Server Platform		On Premise / Cloud
	Face.	1:N	30,000 (50,000 Option)
	Face (Based on one face	1:1	100,000
	Template per User)	TAR	97.99%
	FingerPrint (Based on two Fingerprint Template per User)	FAR 1:N	0.0001%
Capacity		1:1	500,000
		TAR	99.9%
		FAR	0.00001%
	Event Log		10,000,000
Interface	Picture Log		20,000
	ethernet RS-485		10/100M / 1000M 1Port 1 Port
	RS-232		2 Port
	Wiegand		IN/OUT 1Port
	Relay		2
	USB	USB 2.0	Host 1 Port
	USB 3.0		OTG 1 Port (C Type)
	Voltage		DC 15V~24V
Power		Current	Max 1.5A @DC15V

#### **Possible Integration**



Integration for measuring personnel temperature

#### XScan-FQ



Support Fingerprint & QR Code Authentication

#### XScan-FP



Support Fingerprint Authentication

